



Product certificate K11868-11

Issued 2025-07-01

Replaces K11868/10

Page 1 of 5

Gate valves

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

E. Hawle Armaturenwerke GmbH

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline:

BRL-K602: "Valves and other accessories for drinking water transport and drinking water distribution systems" dated 2023-04-21,

which covers the requirements of

EN 1074/2:2000: "Valves for water supply - Fitness for purpose requirements and appropriate verification tests – Part 2: Isolating valves".

Ron Scheepers
Kiwa

Publication of this certificate is allowed.

Advice: consult www.kiwa.com in order to ensure that this certificate is still valid.

CERTIFICATE

287180711

Kiwa Nederland B.V.

Sir Winston Churchillaan 273
Postbus 70
2280 AB RIJSWIJK
The Netherlands
Tel. +31 88 998 44 00
NL.Kiwa.info@Kiwa.com
www.kiwa.com

Company

E. Hawle Armaturenwerke GmbH
Wagrainer Straße 13
4840 VÖCKLABRUCK
Austria
Tel. +43 7672/725760
hawle@hawle.at
www.hawle.com



Certification process
consists of initial and
regular assessment of:

- quality system
- product

Gate valves

PRODUCT SPECIFICATION

The products mentioned below belong to this product certificate.

The gate valves are assembled with the application of lubrication; Unisilikon L641.

Type 4000E1

PN 10 and PN 16, flanges.

DN 50
 DN 65
 DN 80
 DN 100
 DN 125
 DN 150
 DN 200
 DN 250
 DN 300

Type 4000E1+

DN 50
 DN 65
 DN 80
 DN 100
 DN 125
 DN 150
 DN 200
 DN 250
 DN 300

Type 4000E2

PN 16 - FTF basic series 14

DN 50
 DN 65
 DN 80
 DN 100
 DN 125
 DN 150
 DN 200
 DN 250
 DN 300
 DN 350
 DN 400
 DN 500
 DN 600

Type 4700E2

PN 16 - FTF basic series 15

DN 50
 DN 65
 DN 80
 DN 100
 DN 125
 DN 150
 DN 200
 DN 250
 DN 300
 DN 400
 DN 450
 DN 500
 DN 600

Type 4700E1

DN 50
 DN 65
 DN 80
 DN 100
 DN 125
 DN 150
 DN 200

Type 4700E1+

DN 50
 DN 65
 DN 80
 DN 100
 DN 125
 DN 150
 DN 200

Type 4700E3

PN 10 en PN 16

DN 50
 DN 65
 DN 80
 DN 100
 DN 125
 DN 150
 DN 200
 DN 250
 DN 300
 DN 400
 DN 450
 DN 500
 DN 600

Type 4343E3

PN 16

Connection end PVC-U and PE

DN/ Ø pipe 80/90
 DN/ Ø pipe 100/ 110, DN50, DN80, DN100
 DN/ Ø pipe 100/ 125, DN100,
 DN/ Ø pipe 150/ 160, DN80, DN100, DN150
 DN/ Ø pipe 200/ 225, DN80, DN100

Gate valves

Type 4000E3

PN 10 en PN 16

DN 50

DN 65

DN 80

DN 100

DN 125

DN 150

DN 200

DN 250

DN 300

DN 350

DN 400

DN 500

DN 600

Type 4040E3

PN 16

Connection end PVC-U and PE

DN/ Ø pipe 50/ 63

DN/ Ø pipe 65/ 75

DN/ Ø pipe 80/ 90

DN/ Ø pipe 100/ 110

DN/ Ø pipe 100/ 125

DN/ Ø pipe 125/ 125

DN/ Ø pipe 125/ 140

DN/ Ø pipe 150/ 160

DN/ Ø pipe 150/ 180

DN/ Ø pipe 200/ 200

DN/ Ø pipe 200/ 225

DN/ Ø pipe 200/ 250

DN/ Ø pipe 250/ 250

DN/ Ø pipe 250/ 280

DN/ Ø pipe 300/ 315

DN/ Ø pipe 350/ 400

PRODUCT SPECIFICATION (continued)

Type 4040E2

PN 16 Socket - Socket

Ø 63 (DN 50)

Ø 75 (DN 65)

Ø 90 (DN 80)

Ø 110 (DN 100)

Ø 125 (DN 100)

Ø 125 (DN 125)

Ø 140 (DN 125)

Ø 160 (DN 150)

Ø 180 (DN 150)

Ø 200 (DN 200)

Ø 225 (DN 200)

Ø 250 (DN 250)

Ø 280 (DN 250)

Ø 315 (DN 300)

Type 4041E2

PN 16 Flange - Socket

DN 50 / Ø 63

DN 65 / Ø 75

DN 80 / Ø 63

DN 80 / Ø 75

DN 80 / Ø 90

DN 100 / Ø 110

DN 100 / Ø 125

DN 125 / Ø 140

DN 150 / Ø 160

DN 150 / Ø 180

DN 200 / Ø 200

DN 200 / Ø 225

DN 250 / Ø 250

DN 250 / Ø 280

DN 300 / Ø 315

Type 4041 E3

PN 16

Flange / Connection end PVC-U and PE

DN 50 / Ø 63

DN 65 / Ø 75

DN 80 / Ø 90

DN 100 / Ø 110

DN 100 / Ø 125

DN 125 / Ø 140

DN 150 / Ø 160

DN 150 / Ø 180

DN 200 / Ø 200

DN 200 / Ø 225

DN 250 / Ø 250

DN 250 / Ø 280

DN 300 / Ø 315

Gate valves

Type 4343E2 Combi-T

PN 16 Socket – Socket - Socket

Ø 90 (DN 80) - Ø 90 (DN 80) - Ø 90
Ø 110 (DN 100) - Ø 110 (DN 100) - Ø 63
Ø 110 (DN 100) - Ø 110 (DN 100) - Ø 90
Ø 110 (DN 100) - Ø 110 (DN 100) - Ø 110
Ø 160 (DN 150) - Ø 160 (DN 150) - Ø 90
Ø 160 (DN 150) - Ø 160 (DN 150) - Ø 110
Ø 160 (DN 150) - Ø 160 (DN 150) - Ø 160
Ø 225 (DN 200) - Ø 225 (DN 200) - Ø 90
Ø 225 (DN 200) - Ø 225 (DN 200) - Ø 110

Type 2630, plastic body

PN 16, socket – socket

DN 20 ($\frac{1}{2}$ "),
DN 25 ($\frac{3}{4}$ "),
DN 32 (1"),
DN 40 ($1\frac{1}{4}$ "),
DN 50 ($1\frac{1}{2}$ "),
DN 60 (2").

Gate valves

Fitness for contact with drinking water

This product is approved on the basis of the requirements for hygienic aspects set in the "Regeling materialen en chemicaliën drink- en warm tapwatervoorziening" ("Materials and chemicals in the supply of drinking water and warm tap water Regulation" dated 01-07-2017; published in the Government Gazette).

These hygienic aspects are based on two main criteria. The product shall permanently comply with:

- The product recipe approved during the assessment procedure. This recipe is not to be changed without prior approval by Kiwa according to the Kiwa approval procedure for the hygienic aspects;
- Specific product requirements for the hygienic aspects.

The recipe and specific product requirements are laid down in the for confidentiality reasons undisclosed 'appendix hygienic aspects' to this certificate.

MARKING

The Kiwa®-mark products are marked with the word mark "KIWA 

Place of the mark: on the body or specification plate

Compulsory specifications:

- name or mark of manufacturer: on the body or specification plate;
- identification of the shell material(s): on the body or specification plate;
- nominal size "DN ...": on the body or specification plate;
- nominal working pressure "PN ...": on the body or specification plate;
- identification of the year of manufacture: on the body or specification plate;
- number of the relevant part of the EN1074: on the body or specification plate.

Method of marking:

- Non-erasable;
- visible after assembly.

APPLICATION AND USE

Gate valves are designed to, both underground as over ground, be used in pipes for drinking water or raw material for drinking water, with a maximum medium temperature of 30 °C. The valves are designed to open or shut off the pipes and not for regulation purposes.

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- E. Hawle Armaturenwerke GmbH
- and, if necessary,
- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.